

Amendments to the Drawings:

The attached sheet of drawings includes changes to Figure 6. This sheet replaces the original sheet.

Attachment

Amendment to the Abstract:

The Abstract has been amended. A revised Abstract is attached.


Attachment

A compact tripod ~~(1) comprises~~includes at least three legs ~~(2) converging~~ on a spider ~~(3) and~~ hinged thereto at one end by ~~means of a~~ corresponding hinge ~~sleeve means (13) and fork member counter means (15), and a~~ A support (5) is provided for a head ~~(6) mounted~~ on the spider ~~(3) in a position such that this it projects from the spider opposite the legs (2) when the tripod is open in an operating position. The hinge sleeve means (13) and counter means (15) fork member are designed to allow the legs to be folded back from the ~~said~~ part of the support ~~(5) when the tripod is closed in a non-operating position. Additionally, the hinge sleeve means (13) and fork member counter means (15) comprise~~ include a toothed ~~means (27,28) element~~ and a corresponding stop ~~means (25) for the toothed means (27,28) element~~ which are capable of interacting together to limit the extent by which the legs ~~(2) open with respect to the spider (3).~~~~

Remarks/Arguments:

By the Preliminary Amendment, the specification and the Abstract have been amended to place the application in better condition for examination and allowance. Applicant has amended Figure 6 to indicate reference numerals "30" and "33." This is not the addition of new matter, since these reference elements are disclosed in the specification and claims. Claims 1 through 10 have been amended and claims 11 through 20 have been added to avoid multiple dependent claims, remove element numbers and otherwise comply with the requirements and standards of U.S. Patent and Trademark Office practice. Entry of this Preliminary Amendment and issuance of a first office action on the merits are requested.

Respectfully submitted,



Daniel N. Calder, Reg. No. 27,424
Attorney for Applicant

DNC/mhs

Attachments: Abstract
Substitute Specification
Substitute Specification w/revision marks
1 Replacement Drawing Sheet

Dated: July 10, 2006

<input checked="" type="checkbox"/> P.O. Box 980 Valley Forge, PA 19482 (610) 407-0700	<input type="checkbox"/> P.O. Box 1596 Wilmington, DE 19899 (302) 778-2500
--	--

The Director is hereby authorized to charge or credit Deposit Account No. **18-0350** for any additional fees, or any underpayment or credit for overpayment in connection herewith..

EXPRESS MAIL


Mailing Label Number:

EV 058797226 US

Date of Deposit:

July 10, 2006

I hereby certify that this paper and fee are being deposited, under 37 C.F.R. § 1.10 and with sufficient postage, using the "Express Mail Post Office to Addressee" service of the United States Postal Service on the date indicated above and that the deposit is addressed to the Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.



Dennis McDermott

SUBSTITUTE SPECIFICATION WITH REVISION MARKS

10/585541
1AP20 Rec'd PCT/PTO 10 JUL 2006**COMPACT TRIPOD**

This application is a U.S. National Phase Application of PCT International Application PCT/EP2005/000022.

Technical fieldField

This invention relates to a tripod, designed particularly but not exclusively for the support of optical and/or photographic equipment, ~~including the features mentioned in the precharacterising clause of the principal claim.~~ In this context the term "tripod" is to be understood to indicate a support including at least three legs which converge in a spider to which the legs are hinged at one end.

Technological backgroundBackground

Within this specific technical field a need has been felt to provide tripods which are particularly compact when closed into a carrying position.

On the other hand it is likewise required that tripods should extend to a maximum when open in the operating position. The two requirements are obviously conflicting.

In order to reconcile these two resort conditions, there have been ~~it is known to realize~~ tripods with telescopic legs with multiple sections or threaded portions which have minimum dimensions when in the closed position. The number of threaded portions on each leg is however limited, both by technical and dimensional reasons and by reasons of an economic nature. Legs with four or five telescopic sections generally represent the normal technical limit. In order to further reduce the dimensions of tripods in the closed position, arrangements have been

designed which make it possible to partly retract the head support into the spider. The further benefit which can be achieved in this way is however relatively small.

~~A~~An example of a conventional tripod including the features of the preamble of claim 1 is described for example in US Patent No. 4,886,230.

Brief Summary of the invention

The technical problem considered by this invention is that of providing a tripod which is structurally and functionally designed to overcome all the disadvantages mentioned with reference to the known art while at the same time minimising dimensions in the closed position.

This problem has been overcome by the invention through a tripod constructed according to the following claims which includes at least three legs converging in a spider to which the legs are hinged at one end through corresponding hinge means and counter-means. The tripod of the present invention includes a support for a head mounted in the spider in a position such that the support projects from the spider on a side opposite the legs when the tripod is open in an operating position. The hinge means and counter-means are designed to allow the legs to be folded back from that part of the support when the tripod is closed in a non-operating position. The hinge means and counter-means include toothed means and corresponding stop means for the toothed means which are capable of interacting together to limit the extent to which the legs open with respect to the spider.

Brief description of the drawings

The advantages and characteristics of the present invention will become clear from the following detailed description which is given with reference to the appended drawings which are provided purely by way of non-limiting example and in which:

- Figure 1 is a view in elevation of a tripod according to the invention in the open operating position (with legs retracted),
- Figure 2 is an identical view of the tripod in Figure 1 in the closed non-operating position,
- Figure 3 is a perspective view on a magnified scale of a detail of the tripod in Figure 2 (closed position),
- Figures 4 and 5 are perspective views of the same detail in Figure 3 in two different opening positions,
- Figure 6 is a view in axial cross-section of the tripod in the preceding figures in the closed position.

Preferred embodimentsEmbodiments ofOf theThe inventionInvention

In the figures, 1 indicates as a whole a tripod mainly but not exclusively intended for the support of optical and/or photographic equipment constructed according to this invention.

Tripod 1 comprises three identical legs, all indicated by 2, converging on a spider 3 to the ~~centre~~center of which a column 4 is movably attached. Column 4 has a support 5 at one end for a head 6 which is in turn provided with a plate 7 on which the equipment in use can be removably fixed. Plate 7 can be orientated within a substantially hemispherical space through a spherical joint which is not shown. One of the possible orientation positions is that shown in Figure 2, with the tripod closed, to which reference will be made below.

Column 4 is movably guided within a central hub 8 of spider 3 and can be ~~immobilised~~immobilized in an adjustable position through tightening a collar 9. On the side opposite head 6 the latter is provided with a disc-shaped stop 10 surrounded around its perimeter by a resilient elastic ring 11.

Spider 3 comprises three equally spaced arms 12 extending radially from hub 8 and each bearing a hinge sleeve 13. A fork member 15 which is shoed through a tubular length 16 onto the free end of the outermost section 17 (or portion) of corresponding leg 2 is hinged on sleeve 13 through a screw pin 14. Sleeve 13 and fork member 15 constitute respectively hinge means and counter means of each leg 2 to the spider 3.

Legs 2 comprise a plurality of sections or portions 18, 19, 20 and 21 which are telescopically inserted into each other and can be extracted through adjustable extension with the possibility of relative ~~immobilisation~~immobilization through corresponding collar locks 22 which are functionally identical to the one on column 4.

Between the tines 23 of fork member 15 there is a flat surface 24 on which a lever 25 is hinged through a screw 26. A plurality of teeth 27, 28 which are angularly offset with respect to each other and a cylindrical length 29 referred to below as the free length are provided on the outer mantle of hinge sleeve 13. Teeth 27, 28, the free length and hinging pin 14 are coaxial with each other.

Lever 25 can be moved by means of an operating appendage 30 which is accessible from outside the tripod when in the open position, into at least three operating positions in which its intermediate section bearing a shoulder 33 is positioned on the rotation trajectory of teeth 27, 28 or the free length in order to restrict the swing of legs 2 with respect to spider 3 acting as a stop for teeth 27, 28 or to permit legs 2 to rotate completely back on themselves when the aforesaid shoulder lies opposite cylindrical free length 29, against which it does not abut. Lever 25 is resiliently stressed by means of a spring, which is not shown, which acts between the same and surface 24 around screw 26, towards the engaging position with tooth 27 away from free length 29.

As a result of these structural and functional arrangements tripod 1 can be closed from the open operating position in Figure 1 to a non-operating closed

position of minimum dimensions illustrated in Figure 2. The following actions are performed in order to change from one of these positions to the other. Starting from the open operating position in Figure 1, in order to close the tripod column 4 is raised (contrary to what would be expected) into the position of maximum extension, the portions of legs 2 are collapsed telescopically one into another, the lever 25 of each leg is moved in such a way as to position it opposite free length 29 and the corresponding leg is rotated through an angle of more than 90° folding the leg to the same part of support 5 for head 6. In this position the spider and the head disappear completely between the legs of the tripod and do not therefore give rise to any additional dimensions of any kind.

Plate 7 is orientatable substantially at right angles with respect to the column so as to further ~~minimise~~minimize the overall dimensions in the closed position, at the same time ~~maximising~~maximizing the height of the tripod because in this way column 4 can have a longitudinal extension which is substantially identical to the extension of the legs.

The reverse operations are performed in order to open the tripod, swinging the legs around the spider to bring them onto the opposite side of head 6, restricting the opening of the same by appropriately positioning of lever 25 with respect to teeth 27, 28.

Obviously the system governing the amount by which the legs of the tripod open can be wholly different from the lever and teeth system illustrated so far without thereby adversely influencing the function of the invention.

The principal advantage of this tripod lies in ~~maximising~~maximizing the useful height in the open operating position with a concomitant reduction in dimensions in the closed position. In addition to this the tripod is of simple construction, light, easily transportable and easily adjustable in a few operations. Not least, it makes it

possible to keep the head mounted on its support even when the tripod is closed, without interfering with the minimum dimensions.